


GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جى تى سى المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون : 24710120 - فاكس : 24761261
الشويخ - تلفون : 24848285 - فاكس : 24837138
رأس المال : 1,000,000 د.ك - س.ت : 20117

DESCRIPTION :-

GYPSAFILL is a specially formulated joint filler and surfacer for walls, gypsum board, plasterboard, fiberboard among other surfaces. It is non shrinking and does not crack on drying. GYPSAFILL adheres very well to prepared surfaces. It is based on a new technological concept making it possible to fill deep crevices in minimum of applications.

ADVANTAGES :-

- ☐ Rapid setting.
- ☐ Does not crack even in very high thickness.
- ☐ Does not shrink.
- ☐ Excellent adhesion on substrates.
- ☐ Tough, Sandable finish.
- ☐ Uniform fast drying.

TECHNICAL SPECIFICATION :-

- ☐ Form supplied : Putty
- ☐ Colour : Creamy White.
- ☐ S.G. : Approx 1.5-1.53

APPLICATION PROCEDURE :-

Fill clean groove with paste then place polyester mesh on top embedding it in paste. Follow by a very thin application of GYPSAFILL or Acrylic Putty on top of mesh. Let dry.

DRYING TIME :-

1½ hours at room temperature (25°C) shortens with higher ambient temperatures.

SANDING INTERVAL :-

Sandable after around 2 hrs. at room temperature.

OVER COATING INTERVAL :-

Can be over coated after complete drying.

COVERAGE – GYPSUM BOARD JOINTS :-

For standard joint grooves coverage is from 5.00-5.50 meter length per 1 kg. GYPSAFILL approx.

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون: 24710120 - فاكس: 24761261
الشويخ - تلفون: 24848285 - فاكس: 24837138
رأس المال: 1,000,000 د.ك - س.ت: 20117

APPLICATION CONDITIONS :-

At a temperature ranging 5°C (41°F) to 40°C (104 °F) . Relative humidity is below 75%.

STORAGE & HANDLING :-

Product must be stored as per local regulations and should be kept in dry well ventilated location far from heat and direct sunlight. Can should be tightly closed after use. Mix well before use. Storage temperature range between 5°C (41°F) to 40°C (104 °F).

SAFETY PRECAUTIONS:

The following notes should be considered when using/applying material:-

- Take precautions to prevent material entering the eyes (goggles should be worn, irrigate the eyes with water when become contaminated and obtain medical care at once).
- Take precautions to avoid skin contact (gloves should be worn, barrier cream should be used).
- Ensure that repeated contact of paint with skin is avoided.
- Provide adequate ventilation. (Face masks must be worn).
- Keep away from sparks and open flames (for solvent-based materials).

DISCLAIMER:

- The information given in this data sheet is for guidance only and is done to the best of our knowledge at the date of printing/issuing.
- GTC reserves the right to change the content of this data without any prior notice.
- Since we have no control over either the nature or condition of the substrate or different factors which affect the use and application of our products; therefore, no liability can be accepted on basis of this data sheet, unless we specifically agree in writing from us as to the suitability of the recommended product for the intended purpose; and furthermore, application of this product should be carried out under our control and direct supervision.
- Product data are subject to change without notice and become void five years from the date of issue.

PACKING

- ♦ 5 kg Gallon
- ♦ 25 kg Drum

ISSUANCE DATE

: August 2017 .

ORIGIN

: Manufacture in Kuwait By GTC Paints Company Ltd.

ADDRESS

: **GTC PAINTS COMPANY LTD.**

P. O. Box 24445 Safat, 13105 Safat, Kuwait

Tel : 24710120/24710170 - Fax : 24761261 .

Email : sales @ gtcpaints.com