

## GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait  
Sabhan Tel.: 24710120 - Fax : 24761261  
Shuwaikh Tel.: 24848285 - Fax : 24837138  
Capital : K.D. 1,000,000 - C.R.: 20117



## شركة أصباغ جى تى سى المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت  
صباحان - تلفون : 24710120 - فاكس : 24761261  
الشويخ - تلفون : 24848285 - فاكس : 24837138  
رأس المال : 1,000,000 د.ك - س.ت : 20117

# GETEX

## NEOPRENE CONTACT ADHESIVE

### Product Description :-

Getex is a high quality, one pack general purpose adhesive. It consists of a blend of synthetic rubber (neoprene) and resin solution particularly for bonding a wide variety of materials.

### Special Features :-

GTC Getex due to its special formulation gives a high bonding strength in a short time allowing immediate handling of bonded materials. However it's maximum strength is attained after approximately 48 hours at normal room temperature.

### Area of Use :-

Getex is used almost every where. In homes, offices, workshops and constructions sites. Getex is typical for use in carpentry and decorative works for bonding laminated plastics for working tops and many rigid plastics such as PVC & ABS to wood, metal and all types of boards.

Getex is also used for fixing carpets, footwear and leather industry, automotive, caravan furniture, paper and art works, preventing ground water in constructions and buildings, and many other industries.

It is not suitable for use on expanded polystyrene or any other materials which are subjected to attack by organic solvents.

### Product Data :-

<b>Appearance</b>	: Off White to amber.
<b>Consistency</b>	: Getex is supplied at 15 to 20 poise viscosity which is suitable for application by brush or serrated spreader.
<b>Odour</b>	: Odour of organic solvents, particularly of Ketones and esters.
<b>Flash Point</b>	: Highly flammable material.
<b>Bond Strength</b>	: Shear strength 25mmx25mm. Bonded area. Laminated plastic / plywood 165 KGF. Laminated plastic / mild steel 185 KGF.
<b>Coverage</b>	: 5.5 SQ MT/LTR. Approx.

### Standards :

- All phases of the installation should comply with the following standards and any subsequent amendments.
- British standard code of practice CP 102:1973 protection of building against water from the ground.
- British standard code of practice CP203:part 2:1972-sheet and tile flooring.
- Code of practice BS5325 : 1976 – installation of textile floor coverings.
- CFA flooring compendium for architects specifies.

# GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait  
Sabhan Tel.: 24710120 - Fax : 24761261  
Shuwaikh Tel.: 24848285 - Fax : 24837138  
Capital : K.D. 1,000,000 - C.R.: 20117



## شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت  
صباحان - تلفون : 24710120 - فاكس : 24761261  
الشويخ - تلفون : 24848285 - فاكس : 24837138  
رأس المال : 1,000,000 د.ك - س.ت : 20117

### Application Details :-

- Surface Preparation** : All surfaces must be clean, dry and free from Loose particles and grease.  
It is recommended that smooth or polished surfaces should be roughed with fine abrasive paper followed by dusting off.
- Application of Adhesive** : Apply a thin even film of adhesive to both surfaces by brush or serrated spreader.
- Assembly** : When touch dry, the coated surfaces can be positioned and pressed together.  
It is important that the two surfaces are lined up accurately before pressing together because the adhesive provides an instant strong bond on contact.
- Note** : Application should be carried out in well ventilated conditions and great care should be taken that there are no make flames, pilot lights or other sources of ignition near by.
- Storage** : When stored in original unopened container in a cool dry place has a shelf life at least six months. The storage conditions should be suitable for highly flammable materials.

### APPLICATION CONDITIONS :-

At a temperature ranging 5°C (41°F) to 40°C (104 °F) . Relative humidity is below 75%.

### STORAGE & HANDLING :-

Product must be stored as per local regulations and should be kept in dry well ventilated location far from heat and direct sunlight. Can should be tightly closed after use. Mix well before use. Storage temperature range between 5°C (41°F) to 40°C (104 °F).

### SAFETY PRECAUTIONS:

The following notes should be considered when using/applying material:-

- Take precautions to prevent material entering the eyes (goggles should be worn, irrigate the eyes with water when become contaminated and obtain medical care at one).
- Take precautions to avoid skin contact (gloves should be worn, barrier cream should be used).
- Ensure that repeated contact of paint with skin is avoided.
- Provide adequate ventilation. (Face masks must be worn).
- Keep away from sparks and open flames (for solvent-based materials).

### DISCLAIMER:

- The information given in this data sheet is for guidance only and is done to the best of our knowledge at the date of printing/issuing.
- GTC reserves the right to change the content of this data without any prior notice.
- Since we have no control over either the nature or condition of the substrate or different factors which affect the use and application of our products; therefore, no liability can be accepted on basis of this data sheet, unless we specifically agree in writing from us as to the suitability of the recommended product for the intended purpose; and furthermore, application of this product should be carried out under our control and direct supervision.
- Product data are subject to change without notice and become void five years from the date of issue.

### **PACKING**

: ♦ Gallon (3 kg) .

### **ISSUANCE DATE**

: August 2017 .

### **ORIGIN**

: Manufacture in Kuwait By GTC Paints Company Ltd.

### **ADDRESS**

: **GTC PAINTS COMPANY LTD.**

P. O. Box 24445 Safat, 13105 Safat, Kuwait

Tel : 24710120/24710170 - Fax : 24761261 .

Email : sales @ gtcpaints.com