

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون: 24710120 - فاكس: 24761261
الشويخ - تلفون: 24848285 - فاكس: 24837138
رأس المال: 1,000,000 د.ك - س.ت: 20117

GET-A-SEAL VS-30

Vapour Barrier Adhesive for A/C Ducts

PRODUCT DESCRIPTION

Get-A-Seal VS-30 adhesive is a water base duct sealant which provides a protective layer that acts as a vapour barrier for air conditioning duct joints for hot and chilled water systems.

SPECIAL FEATURES

- ☐ Get-A-Seal VS-30 adhesive films and layers remain flexible and functional through a wide range of temperature.
- ☐ Provides a protective finish which acts as a vapour barrier for duct joints.
- ☐ Resists high humidity and water.
- ☐ Excellent for sealing and joining all types of insulation materials.
- ☐ Get-A-Seal VS-30 adhesive has a heavy thixotropic body which will not sag or run which makes it ideal for vertical as well as horizontal surfaces.
- ☐ Can be supplied in an antifungal type with broad Biocidal activity. (GET-A-SEAL VS-30 BI)

AREA OF USES

Get-A-Seal VS-30 adhesive seals expansion joints in many types of materials against humidity and water vapour ingress, it remains flexible and functional through a wide temperature range. It can be used on polyurethane, polystyrene, mineral wool, fibrous glass, and other insulation materials.

PRODUCT DATA

Colour	: Grey.
Consistency	: Thixotropic Paste.
Specific Gravity	: 1.45 + 0.05 kg /ltr.
Odour	: Slight odour when wet, odorless when dry.
Drying Time	: 2 hrs. touch dry, about 12 hrs. through dry depending on temperature, humidity and film thickness.
Coverage	: 160 gram for 1x1 cm linear joint.
Flammability	: Non flammable, water based.
Clean Up	: Water when wet or GTC Cleaner when dry.

APPLICATION DETAILS

- ☐ **Surface preparation**
The surface to be sealed must be sound, dry and free from oil grease, dust and other contamination.
- ☐ **Application of Adhesive**
Get-A-Seal VS-30 adhesive duct sealant can be applied with putty knife spatula, trowel, caulking gun or can be extruded, it has a heavy thixotropic body and will not sag or run.

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جى تى سى المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون : 24710120 - فاكس : 24761261
الشويخ - تلفون : 24848285 - فاكس : 24837138
رأس المال : 1,000,000 د.ك - س.ت : 20117

APPLICATION CONDITIONS :-

At a temperature ranging 5°C (41°F) to 40°C (104 °F) . Relative humidity is below 75%.

STORAGE & HANDLING :-

Product must be stored as per local regulations and should be kept in dry well ventilated location far from heat and direct sunlight. Can should be tightly closed after use. Mix well before use. Storage temperature range between 5°C (41°F) to 40°C (104 °F).

STANDARDS & APPROVALS

Supportive information is available upon request.

Please consult with GTC Technical Service Dept.

SAFETY PRECAUTIONS:

The following notes should be considered when using/applying material:-

- Take precautions to prevent material entering the eyes (goggles should be worn, irrigate the eyes with water when become contaminated and obtain medical care at one).
- Take precautions to avoid skin contact (gloves should be worn, barrier cream should be used).
- Ensure that repeated contact of paint with skin is avoided.
- Provide adequate ventilation. (Face masks must be worn).
- Keep away from sparks and open flames (for solvent-based materials).

DISCLAIMER:

- The information given in this data sheet is for guidance only and is done to the best of our knowledge at the date of printing/issuing.
- GTC reserves the right to change the content of this data without any prior notice.
- Since we have no control over either the nature or condition of the substrate or different factors which affect the use and application of our products; therefore, no liability can be accepted on basis of this data sheet, unless we specifically agree in writing from us as to the suitability of the recommended product for the intended purpose; and furthermore, application of this product should be carried out under our control and direct supervision.
- Product data are subject to change without notice and become void five years from the date of issue.

PACKING

: ☐ 5 KG Gallon.

ISSUANCE DATE

: August 2017 .

ORIGIN

: Manufacture in Kuwait By GTC Paints Company Ltd.

ADDRESS

: **GTC PAINTS COMPANY LTD.**

P. O. Box 24445 Safat, 13105 Safat, Kuwait

Tel : 24710120/24710170 - Fax : 24761261 .

Email : sales @ gtcpaints.com