

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جى تى سى المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون: 24710120 - فاكس: 24761261
الشويخ - تلفون: 24848285 - فاكس: 24837138
رأس المال: 1,000,000 د.ك - س.ت: 20117

Get-A-Seal One Component Acrylic Sealant

PRODUCT DESCRIPTION :-

A general purpose mastic adhesive used internally and externally for sticking sealing and water proofing low movement joints, bricks work, Precast construction and round window and door frames. It adheres to most building surfaces and as an Acrylic copolymer base product, it cures to form a flexible and water proofing seal.

SPECIAL FEATURES :-

- ☐ GTG Get-A-Seal adhesive sealant is one component easy to fill.
- ☐ Water proofing and water sealant after curing.
- ☐ Durable flexible film.
- ☐ Easy to clean by water before curing.
- ☐ Can be thinned by water to make primer.

PRODUCT DATA :-

Appearance	: A smooth viscous paste.
Colour	: White, Grey.
Specific Gravity	: 1.5
Solid Content	: 80 + 2%.
Sag	: no sag in 30 mm channel.
Skinning time	: 30 minutes.
Curing time	: Cures by evaporation of water 1-2 weeks depending upon temp.
Flammability	: Non flammable (water born).
Application	: Do not use below 5 °C.
Weight Loss	: 25 % approx.

CONSUMPTION :-

The following table shows the amount of consumed material in grams for linear meter of joints.

Width/depth	1 CM	1.5 CM	2.0 CM	2.5 CM	3.0 CM
1.0 CM	160 GM	240 GM	320 GM	400 GM	480 GM
1.5 CM	240 GM	320 GM	480 GM	600 GM	720 GM
2.0 CM	320 GM	480 GM	640 GM	800 GM	960 GM
2.5 CM	400 GM	600 GM	800 GM	1000 GM	1200 GM
3.0 CM	480 GM	720 GM	960 GM	1200 GM	1440 GM

STANDARDS & APPROVALS:

Supportive information is available upon request to establish an assessment to be acquired as with regards to product's compliance with/to a particular authority's queries /specifications. *Please consult with GTC Technical Service Dept.*

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جى تى سى المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون: 24710120 - فاكس: 24761261
الشويخ - تلفون: 24848285 - فاكس: 24837138
رأس المال: 1,000,000 د.ك - س.ت: 20117

APPLICATION DETAILS :-

- ☐ **Surface preparation :-**
Surface should be clean and free from oil and grease.
- ☐ Priming is not generally required on porous surfaces. When necessary, diluted with water as (1:10).
- ☐ GTC Get-A-Seal can be applied by hand or air operated caulking. Sealant is pushed firmly into the joint and wetted surface, tooling should be carried out immediately using joint shaping tools soaked in detergent solution.

APPLICATION CONDITIONS :-

At a temperature ranging 5°C (41°F) to 40°C (104 °F) . Relative humidity is below 75%.

STORAGE & HANDLING :-

Product must be stored as per local regulations and should be kept in dry well ventilated location far from heat and direct sunlight. Can should be tightly closed after use. Mix well before use. Storage temperature range between 5°C (41°F) to 40°C (104 °F).

SAFETY PRECAUTIONS:

The following notes should be considered when using/applying material:-

- (a) Take precautions to prevent material entering the eyes (goggles should be worn, irrigate the eyes with water when become contaminated and obtain medical care at once).
- (b) Take precautions to avoid skin contact (gloves should be worn, barrier cream should be used).
- (c) Ensure that repeated contact of paint with skin is avoided.
- (d) Provide adequate ventilation. (Face masks must be worn).
- (e) Keep away from sparks and open flames (for solvent-based materials).

DISCLAIMER:

- The information given in this data sheet is for guidance only and is done to the best of our knowledge at the date of printing/issuing.
- GTC reserves the right to change the content of this data without any prior notice.
- Since we have no control over either the nature or condition of the substrate or different factors which affect the use and application of our products; therefore, no liability can be accepted on basis of this data sheet, unless we specifically agree in writing from us as to the suitability of the recommended product for the intended purpose; and furthermore, application of this product should be carried out under our control and direct supervision.
- Product data are subject to change without notice and become void five years from the date of issue.

Packing

: ♦ Drum 25 kg.

Issue Date

: August 2017.

Origin

: Manufacture in Kuwait By GTC Paints Company Ltd.

Address

: **GTC PAINTS COMPANY LTD.**

P.O.BOX 24445 Safat, 13105 Safat, Kuwait

Tel : 24710120/24710170 - Fax : 24761261

Email : sales @ gtcpaints.com.