

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون: 24710120 - فاكس: 24761261
الشويخ - تلفون: 24848285 - فاكس: 24837138
رأس المال: 1,000,000 د.ك - س.ت: 20117

* * **DL SYLOX** * *

PRODUCT DESCRIPTION:

A siloxane water-based paint ideal for interior and exterior use, it is best solution to protect surfaces and decorative coating such as DL Travertine Ferenza, Adobeetc, and allow to create waterproof surface and gives the finishing particular shades .

SPECIAL FEATURES:

- ☐ Easy to apply.
- ☐ Neither flammable nor hazardous, being as mindful of the environment as of personal health.
- ☐ Is ideal finishing to protect decorated coating such as DL Travertine and gives the surface elegant shades of colour.
- ☐ Excellent weather resistance.
- ☐ Washable and water proof.

AREA OF USE:

As a protective/decorative coating for exterior and interior surfaces.

PRODUCT DATA:

FINISH	:	MATT
COLOUR	:	Clear & according to GTC COLOUR CARD , Special colours are available upon request .
PRODUCT WEIGHT	:	1.02 Kg/Ltr.
THEO. COVERAGE	:	19 m ² / ltr. per coat Practical coverage primarily depends upon nature/degree of surface porosity, method of application and site conditions.
FLASH POINT	:	Non-flammable (water-borne product)

DRYING TIME:

SUBSTRATE TEMPERATURE	TOUCH DRY	HARD DRY	OVERCOATING INTERVALS	
			MINIMUM	MAXIMUM
10 °C (50 °F)	3 hrs.	5 hrs.	5 hrs.	IND.
25 °C (77 °F)	2 hrs.	4 hrs.	4 hrs.	IND.
40 °C (104 °F)	1 hour	3 hrs.	3 hrs.	IND.

SURFACE PREPARATION:

The surface should be clean and completely dry.

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جى تى سى المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون : 24710120 - فاكس : 24761261
الشويخ - تلفون : 24848285 - فاكس : 24837138
رأس المال : 1,000,000 د.ك - س.ت : 20117

APPLICATION DETAILS:

Intended for one or two coats after thinning of water by volume from 50%-100% depending by the desired effect.

CLEANING:

For cleaning tools and equipment use fresh water only.

APPLICATION CONDITIONS :-

At a temperature ranging 5°C (41°F) to 40°C (104 °F) . Relative humidity is below 75%.

STORAGE & HANDLING :-

Product must be stored as per local regulations and should be kept in dry well ventilated location far from heat and direct sunlight. Can should be tightly closed after use. Mix well before use. Storage temperature range between 5°C (41°F) to 40°C (104 °F).

STANDARDS & APPROVALS:

Supportive information is available upon request to establish product compliance with a particular specification. **Please consult with GTC Technical Service Dept.**

SAFETY PRECAUTIONS:

The following notes should be considered when using/applying painting material:-

- Take precautions to prevent material entering the eyes (goggles should be worn, irrigate the eyes with water when become contaminated and obtain medical care at once).
- Take precautions to avoid skin contact (gloves should be worn, barrier cream should be used).
- Ensure that repeated contact of paint with skin is avoided.
- Provide adequate ventilation. (Face masks must be worn).
- Keep away from sparks and open flames (for solvent-based materials).

DISCLAIMER:

- The information given in this data sheet is for guidance only and is done to the best of our knowledge at the date of printing/issuing.
- GTC reserves the right to change the content of this data without any prior notice.
- Since we have no control over either the nature or condition of the substrate or different factors which effect the use and application of our products; therefore, no liability can be accepted on basis of this data sheet, unless we specifically agree in writing as to the suitability of the recommended product for the intended purpose; and furthermore, application of this product should be carried out under our control and direct supervision.
- Product data are subject to change without notice and become void five years from the date of issue.

PACKING : ♦ 2.5 ltr. Can
 : ♦ 15 ltr. Drum
ISSUANCE DATE : August 2017 .
ORIGIN : Manufacture in Kuwait By GTC Paints Company Ltd.
ADDRESS : **GTC PAINTS COMPANY LTD.**
 P.O.Box 24445 Safat, 13105 Safat, Kuwait
 Tel : 24710120/24710170 - Fax : 24761261 .
 Email : sales @ gtcpaints. com.