

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون: 24710120 - فاكس: 24761261
الشويخ - تلفون: 24848285 - فاكس: 24837138
رأس المال: 1,000,000 د.ك - س.ت: 20117

P.V.C. Multi-Purpose Flooring Adhesive

PRODUCTION DESCRIPTION :-

GTC Flooring Adhesive is specially formulated for bonding sheet vinyl covering, foam-back carpet, rubber-backed carpet tiles, PVC tiles, cork floor tiles, fiber glass mesh and wood – block tiles to most surfaces, including concrete, timber, hard board and vinyl.

SPECIAL FEATURES :-

GTC Flooring Adhesive is an acrylic based material with paste like consistency formulated to produce :

- ☐ A high degree of tack in dry film.
- ☐ Excellent bond strength
- ☐ Exceptional resistance to plasticizer migration.

Note :-

Can be used for other special application : i.e. Bonding laminated paper carton, vinyl wall paper etc. please contact our technical department for details.

PRODUCT DATA :-

Appearance	: Light cream colour.
Consistency	: Thin paste.
Odour	: Slight odour when liquid, but odourless once dry.
Open Time	: 20-30 minutes, depending on sight conditions.
Drying Time	: Depends on application method and substrate, normally not longer than 24 hours.
Flash Point	: Flammable in wet state . dry film non flammable.
Water Resistance	: Adhesive is resistant to damp, but continuously wet or damp conditions will damage any floor covering.
Chemicals	: Resistant to most common chemicals, softens in strong organic solvents.
Coverage	: Approximately 5m ² / KG Depends upon porosity of substrate and trowel size.

APPLICATION DETAILS :

- ☐ **Surface Preparation :**
The surface to be sealed must be sound, dry and free from oil grease, dust and other contamination.
- ☐ **Application of Adhesive :**
Spread the adhesive over areas of approximately 1 m² at a time.
Press flooring materials firmly into the adhesive within 20-30 minutes.
Press into position making sure any air bubbles are excluded. Remove excess adhesive immediately with a damp cloth.

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون : 24710120 - فاكس : 24761261
الشويخ - تلفون : 24848285 - فاكس : 24837138
رأس المال : 1,000,000 د.ك - س.ت : 20117

APPLICATION CONDITIONS :-

At a temperature ranging 5°C (41°F) to 40°C (104 °F) . Relative humidity is below 75%.

STORAGE & HANDLING :-

Product must be stored as per local regulations and should be kept in dry well ventilated location far from heat and direct sunlight. Can should be tightly closed after use. Mix well before use. Storage temperature range between 5°C (41°F) to 40°C (104 °F).

Note :

For thin film application diluted the 1 part of PVC adhesive to 3-4 parts of water.

STANDARDS & APPROVALS

Supportive information is available upon request.

Please consult with GTC Technical Service Dept.

SAFETY PRECAUTIONS:

The following notes should be considered when using/applying material:-

- Take precautions to prevent material entering the eyes (goggles should be worn, irrigate the eyes with water when become contaminated and obtain medical care at once).
- Take precautions to avoid skin contact (gloves should be worn, barrier cream should be used).
- Ensure that repeated contact of paint with skin is avoided.
- Provide adequate ventilation. (Face masks must be worn).
- Keep away from sparks and open flames (for solvent-based materials).

DISCLAIMER:

- The information given in this data sheet is for guidance only and is done to the best of our knowledge at the date of printing/issuing.
- GTC reserves the right to change the content of this data without any prior notice.
- Since we have no control over either the nature or condition of the substrate or different factors which affect the use and application of our products; therefore, no liability can be accepted on basis of this data sheet, unless we specifically agree in writing from us as to the suitability of the recommended product for the intended purpose; and furthermore, application of this product should be carried out under our control and direct supervision.
- Product data are subject to change without notice and become void five years from the date of issue.

PACKING

- : ☐ 3½ KG Gallon.
: ☐ 18 KG Drums.

ISSUANCE DATE

: August 2017 .

ORIGIN

: Manufacture in Kuwait By GTC Paints Company Ltd.

ADDRESS

: **GTC PAINTS COMPANY LTD.**

P. O. Box 24445 Safat, 13105 Safat, Kuwait

Tel : 24710120/24710170 - Fax : 24761261 .

Email : sales @ gtcpaints.