

# GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait  
Sabhan Tel.: 24710120 - Fax : 24761261  
Shuwaikh Tel.: 24848285 - Fax : 24837138  
Capital : K.D. 1,000,000 - C.R.: 20117



# شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت  
صباحان - تلفون : 24710120 - فاكس : 24761261  
الشويخ - تلفون : 24848285 - فاكس : 24837138  
رأس المال : 1,000,000 د.ك - س.ت : 20117

## \* \* DL AQUASHEEN \* \*

### PRODUCT DESCRIPTION:

DL Aquasheen is a polyurethane water-based, and ideal finishing for the application of the decorative "DL ARMONI, DL TRAVERTINE, Antique Techniques" for the decoration of floors and walls with a "Limitless effect" for high prestige and elegance in a contemporary style and high tech.

### SPECIAL FEATURES:

- ☐ Clear protection.
- ☐ Good film formation, excellent results of hardness, chemical resistance, abrasion resistance and impact.
- ☐ Easy to apply.
- ☐ Offers a durable and long lasting finish.
- ☐ Excellent graffiti resistance.
- ☐ Excellent cleanability.
- ☐ DL Aquasheen available in Matt, Semi-Gloss and Gloss Finish.
- ☐ Protection for wooden floors (Parquet).

### AREA OF USE:

As a protective/decorative coating for exterior and interior surfaces especially over "DL ARMONI" or Technique Stuccos surfaces on walls and floors.

### PRODUCT DATA:

FINISH	:	AQUASHEEN	Matt
		AQUASHEEN	Semi-Gloss
		AQUASHEEN	Gloss
COLOUR	:	Clear.	
PRODUCT WEIGHT	:	1 Kg/Ltr.	
THEO. COVERAGE	:	14 m <sup>2</sup> / ltr. per coat	
		Practical coverage primarily depends upon nature/degree of surface porosity, method of application and site conditions.	
FLASH POINT	:	Non-flammable (water-borne product)	

### DRYING TIME:

SUBSTRATE TEMPERATURE	TOUCH DRY	HARD DRY	OVERCOATING INTERVALS	
			MINIMUM	MAXIMUM
10 °C (50 °F)	1.5 hrs.	9 hrs.	9 hrs.	48 hrs.
25 °C (77 °F)	1 hour	8 hrs.	8 hrs.	24 hrs.
40 °C (104 °F)	45 min.	7 hrs.	7 hrs.	20 hrs.

# GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait  
Sabhan Tel.: 24710120 - Fax : 24761261  
Shuwaikh Tel.: 24848285 - Fax : 24837138  
Capital : K.D. 1,000,000 - C.R.: 20117



# شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت  
صباحان - تلفون: 24710120 - فاكس: 24761261  
الشويخ - تلفون: 24848285 - فاكس: 24837138  
رأس المال: 1,000,000 د.ك - س.ت: 20117

## SURFACE PREPARATION:

Remove all dust, dirt, oil and grease contamination, loose particles, laitance and old paint...etc, the surface must be smooth and dry.

## APPLICATION DETAILS:

It is Intended for two coats application after thinning of 5% - 10% by volume with fresh water, apply a first coat by Roller of "DL Aquasheen Semi-Gloss" OR "DL Aquasheen Gloss" apply a second coat after at least 8 hours, but not later than 48 hours, apply a second coat, always by Roller, if the application of the second coat runs over the 48 hours, the surface must be sanded before applying the second coat.

## CLEANING:

For cleaning tools and equipment use fresh water only.

## APPLICATION CONDITIONS :-

At a temperature ranging 5°C (41°F) to 40°C (104 °F) . Relative humidity is below 75%.

## STORAGE & HANDLING :-

Product must be stored as per local regulations and should be kept in dry well ventilated location far from heat and direct sunlight. Can should be tightly closed after use. Mix well before use. Storage temperature range between 5°C (41°F) to 40°C (104 °F).

## STANDARDS & APPROVALS:

Supportive information is available upon request to establish product compliance with a particular specification. **Please consult with GTC Technical Service Dept.**

## SAFETY PRECAUTIONS:

The following notes should be considered when using/applying painting material:-

- Take precautions to prevent material entering the eyes (goggles should be worn, irrigate the eyes with water when become contaminated and obtain medical care at once).
- Take precautions to avoid skin contact (gloves should be worn, barrier cream should be used).
- Ensure that repeated contact of paint with skin is avoided.
- Provide adequate ventilation. (Face masks must be worn).
- Keep away from sparks and open flames (for solvent-based materials).

## DISCLAIMER:

- The information given in this data sheet is for guidance only and is done to the best of our knowledge at the date of printing/issuing.
- GTC reserves the right to change the content of this data without any prior notice.
- Since we have no control over either the nature or condition of the substrate or different factors which effect the use and application of our products; therefore, no liability can be accepted on basis of this data sheet, unless we specifically agree in writing as to the suitability of the recommended product for the intended purpose; and furthermore, application of this product should be carried out under our control and direct supervision.
- Product data are subject to change without notice and become void five years from the date of issue.

## PACKING

- ♦ 2.5 ltr. Can
- ♦ 15 ltr. Drum

## ISSUANCE DATE

: August 2017 .

## ORIGIN

: Manufacture in Kuwait By GTC Paints Company Ltd.

## ADDRESS

: **GTC PAINTS COMPANY LTD.**

P.O.Box 24445 Safat, 13105 Safat, Kuwait

Tel : 24710120/24710170 - Fax : 24761261 .

Email : sales @ gtcpaints. com.