

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون: 24710120 - فاكس: 24761261
الشويخ - تلفون: 24848285 - فاكس: 24837138
رأس المال: 1,000,000 د.ك - س.ت: 20117

DL PROMATT

PRODUCT DESCRIPTION:

A clear, water-based decorative finish for indoor use, consisting of water borne polyurethane resins mixed with special additives. Owing to its clear matt look, DL Promatt affords a particular sense of security, an "overcast" look and a pleasant feel.

SPECIAL FEATURES:

- ☐ The finish shields the colored surfaces from dust, smoke, and smudges, hindering the yellowing brought about by aging.
- ☐ Easy to apply and can achieve fine decorations.
- ☐ Fully washable and waterproof.
- ☐ Neither flammable nor hazardous, being a mindful of the environment as of personal health.
- ☐ Gives matt, anti-glaze look, and gives the surface an especially pleasant feeling to touch.

AREA OF USE:

DL Promatt is decorative finish ideal for interior surfaces and may be applied to all kinds of painted or unpainted plasters, plaster boards, and concrete surfaces, as well as wood and metal panels as long as they are treated with appropriate primers.

PRODUCT DATA:

FINISH	:	MATT .
COLOUR	:	CLEAR .
PRODUCT WEIGHT	:	1.04 Kg/Ltr.
THEO. COVERAGE	:	11 m ² / ltr. per coat
Practical coverage primarily depends upon nature/degree of surface porosity, method of application and site conditions.		
FLASH POINT	:	Non-flammable (water-borne product)

DRYING TIME:

SUBSTRATE TEMPERATURE	TOUCH DRY	HARD DRY	OVERCOATING INTERVALS	
			MINIMUM	MAXIMUM
10 °C (50 °F)	3 hrs.	5 hrs.	5 hrs.	IND.
25 °C (77 °F)	2 hrs.	4 hrs.	4 hrs.	IND.
40 °C (104 °F)	1 hour	3 hrs.	3 hrs.	IND.

SURFACE PREPARATION:

Remove all dust, dirt, oil and grease contamination, loose particles, laitance and old paint...etc, the surface must be smooth, dry and completely unimpaired.

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون: 24710120 - فاكس: 24761261
الشويخ - تلفون: 24848285 - فاكس: 24837138
رأس المال: 1,000,000 د.ك - س.ت: 20117

APPLICATION DETAILS:

DL Promatt is ready to use, no need of thinning.

1. APPLICATION OF CONCRETE/PLASTER WALLS :

- | | |
|--|---|
| 1 st Coat | : One coat Acrylic Sealer 100% thinning by volume with water. OR
Penetrol Sealer 25% thinning by volume with water. |
| 2 nd & 3 rd Coat | : One coat Emulsion Paint color . |
| 4 th Coat | : Two coats of DL Promatt . |

CLEANING:

For cleaning tools and equipment use fresh water only.

APPLICATION CONDITIONS :-

At a temperature ranging 5°C (41°F) to 40°C (104 °F) . Relative humidity is below 75%.

STORAGE & HANDLING :-

Product must be stored as per local regulations and should be kept in dry well ventilated location far from heat and direct sunlight. Can should be tightly closed after use. Mix well before use. Storage temperature range between 5°C (41°F) to 40°C (104 °F).

STANDARDS & APPROVALS:

Supportive information is available upon request to establish product compliance with a particular specification. **Please consult with GTC Technical Service Dept.**

SAFETY PRECAUTIONS:

The following notes should be considered when using/applying painting material:-

- Take precautions to prevent material entering the eyes (goggles should be worn, irrigate the eyes with water when become contaminated and obtain medical care at once).
- Take precautions to avoid skin contact (gloves should be worn, barrier cream should be used).
- Ensure that repeated contact of paint with skin is avoided.
- Provide adequate ventilation. (Face masks must be worn).
- Keep away from sparks and open flames (for solvent-based materials).

DISCLAIMER:

- The information given in this data sheet is for guidance only and is done to the best of our knowledge at the date of printing/issuing.
- GTC reserves the right to change the content of this data without any prior notice.
- Since we have no control over either the nature or condition of the substrate or different factors which effect the use and application of our products; therefore, no liability can be accepted on basis of this data sheet, unless we specifically agree in writing as to the suitability of the recommended product for the intended purpose; and furthermore, application of this product should be carried out under our control and direct supervision.
- Product data are subject to change without notice and become void five years from the date of issue.

PACKING : ♦ 2.5 ltr. Plastic Can.
ISSUANCE DATE : August 2017
ORIGIN : Manufacture in Kuwait by GTC Paints Company Ltd.
ADDRESS : **GTC PAINTS COMPANY LTD.**
P.O.Box 24445 Safat, 13105 Safat, Kuwait
Tel : 24710120/24710170 - Fax : 24761261 .
Email : sales @ gtcpaints.com