

## GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait  
Sabhan Tel.: 24710120 - Fax : 24761261  
Shuwaikh Tel.: 24848285 - Fax : 24837138  
Capital : K.D. 1,000,000 - C.R.: 20117



## شركة أصباغ جى تى سى المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت  
صباحان - تلفون: 24710120 - فاكس: 24761261  
الشويخ - تلفون: 24848285 - فاكس: 24837138  
رأس المال: 1,000,000 د.ك - س.ت: 20117

### GET-A-FIX W.R. Water Resistant Ceramic Tile Adhesive

#### PRODUCT DESCRIPTION :-

Get-A-Fix W.R. is ready mixed, with acrylic based copolymer, water-proof, non flammable, paste like consistency, ceramic tile adhesive.

#### SPECIAL FEATURES :-

- ☐ Acrylic – Copolymer based.
- ☐ Specially formulated to suit G.C.C. Climatic condition and BS5385/code of practice.
- ☐ Good working and wet open time.
- ☐ Good slip resistance.
- ☐ Good water resistance after drying 7 days.
- ☐ High adhesive bond strength .
- ☐ GTC Get-A-Fix W.R. will be stand water immersion when it has fully dried. It retains high bond strength in both dry and continuously wet conditions.

#### AREAS OF USES :-

For bonding ceramic wall tiles mosaics to plaster, plywood hard wood, gypsum board, painted surfaces and rendered light concrete blocks. It is suitable for Kitchen and bathrooms.

#### Product Data :-

Binder	: Acrylic copolymer.
Type	: Water base.
Colour	: Off-White.
Consistency	: A stiff paste suitable for application by notched trowel.
Flash Point	: Non flammable.
Specific Gravity	: 1.5 + 0.05 approx.
Coverage	: 1 SQMT/LTR if used with 6mmx6mm notched at 25 mm center covers.

# GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait  
Sabhan Tel.: 24710120 - Fax : 24761261  
Shuwaikh Tel.: 24848285 - Fax : 24837138  
Capital : K.D. 1,000,000 - C.R.: 20117



## شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت  
صباحان - تلفون: 24710120 - فاكس: 24761261  
الشويخ - تلفون: 24848285 - فاكس: 24837138  
رأس المال: 1,000,000 د.ك - س.ت: 20117

### Application Details :-

#### ☐ Surface preparation :-

The surface to be tiled must be sound, flat, dry and free from oil grease, dust and other contamination.

#### ☐ Application of Adhesive :-

The adhesive should be spread on the wall to a depth of 3mm. This operation is immediately followed by combing the adhesive with a notched trowel 6mm wide 6mm deep at 25mm centers. This will produce a series of paroled ribs of adhesive.

#### ☐ Assembly :-

Tiles should be pressed in with sliding and twisting action to the place to achieve a better contact between the back of the tile and adhesive. Ceramic tile should never be fixed with tight joint. After tiling of 24 hrs, front with white cement the joints.

### APPLICATION CONDITIONS :-

At a temperature ranging 5°C (41°F) to 40°C (104 °F) . Relative humidity is below 75%.

### STORAGE & HANDLING :-

Product must be stored as per local regulations and should be kept in dry well ventilated location far from heat and direct sunlight. Can should be tightly closed after use. Mix well before use. Storage temperature range between 5°C (41°F) to 40°C (104 °F).

### Standards & Approvals :-

Supportive information is available upon request to establish and assessment to be acquired as with regards to products compliance with/to a particular authority's queries/specifications.

Please consult with GTC Technical Service Dept.

### SAFETY PRECAUTIONS:

The following notes should be considered when using/applying material:-

- Take precautions to prevent material entering the eyes (goggles should be worn, irrigate the eyes with water when become contaminated and obtain medical care at one).
- Take precautions to avoid skin contact (gloves should be worn, barrier cream should be used).
- Ensure that repeated contact of paint with skin is avoided.
- Provide adequate ventilation. (Face masks must be worn).
- Keep away from sparks and open flames (for solvent-based materials).

### DISCLAIMER:

- The information given in this data sheet is for guidance only and is done to the best of our knowledge at the date of printing/issuing.
- GTC reserves the right to change the content of this data without any prior notice.
- Since we have no control over either the nature or condition of the substrate or different factors which affect the use and application of our products; therefore, no liability can be accepted on basis of this data sheet, unless we specifically agree in writing from us as to the suitability of the recommended product for the intended purpose; and furthermore, application of this product should be carried out under our control and direct supervision.
- Product data are subject to change without notice and become void five years from the date of issue.

### PACKING

- ♦ 5 kg Gallon
- ♦ 25 kg Drum

### ISSUANCE DATE

: August 2017 .

### ORIGIN

: Manufacture in Kuwait By GTC Paints Company Ltd.

### ADDRESS

: **GTC PAINTS COMPANY LTD.**

P. O. Box 24445 Safat, 13105 Safat, Kuwait

Tel : 24710120/24710170 - Fax : 24761261 .

Email : sales @ gtcpaints.co