

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون: 24710120 - فاكس: 24761261
الشويخ - تلفون: 24848285 - فاكس: 24837138
رأس المال: 1,000,000 د.ك - س.ت: 20117

* * DL STARS * *

PRODUCT DESCRIPTION:

A water-borne decorative paint finish for interior use, consisting of water base styrene-Acrylic resins enriched with pre-pigmented beads, metallic pigments, and special fillers. **DL STARS** generates surprisingly nuanced and stunning reflections, producing highly original light mutations that brighten up the rooms and make them look trendy at the same time.

SPECIAL FEATURES:

- ☐ Easy to apply that can achieve great results and crystal fine decorations.
- ☐ Washable and water proof.
- ☐ Neither flammable nor hazardous, being as mindful of the environment as of personal health.
- ☐ Excellent adhesion characteristics and colour retention properties.

AREA OF USE:

DL STARS is decorative finish is ideal for interior surfaces and may applied to all kinds of plasters, plaster boards, and concrete surfaces, as well as wood and metal panels as long as they are treated with appropriate primers.

PRODUCT DATA:

FINISH	:	Crystalline effect.
COLOUR	:	According to GTC COLOUR CARD , Special colours are available upon request .
PRODUCT WEIGHT	:	1.2 Kg/Ltr.
THEO. COVERAGE	:	7 m ² / ltr. per coat Practical coverage primarily depends upon nature/degree of surface porosity, method of application and site conditions.
FLASH POINT	:	Non-flammable (water-borne product)

DRYING TIME:

SUBSTRATE TEMPERATURE	TOUCH DRY	HARD DRY	OVERCOATING INTERVALS	
			MINIMUM	MAXIMUM
10 °C (50 °F)	3 hrs.	5 hrs.	5 hrs.	IND.
25 °C (77 °F)	2 hrs.	4 hrs.	4 hrs.	IND.
40 °C (104 °F)	1 hour	3 hrs.	3 hrs.	IND.

SURFACE PREPARATION:

Remove all dust, dirt, oil and grease contamination, loose particles, laitance and old paint ...etc, the surface must be smooth and dry.

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون: 24710120 - فاكس: 24761261
الشويخ - تلفون: 24848285 - فاكس: 24837138
رأس المال: 1,000,000 د.ك - س.ت: 20117

APPLICATION DETAILS:

1. APPLICATION OF CONCRETE/PLASTER WALLS :

- 1st Coat : One coat Acrylic Sealer 100% thinning by volume with water. **OR**
Penetrol Sealer 25% thinning by volume with water.
2nd Coat : One coat DL ART Primer matching the color of DL STARS finish coat or White.
3rd & 4th Coat : Two coats of DL STARS finish colour, by using brush 35% thinning by volume with water Or one coat without water thinning .

2. APPLICATION OF METALIC SURFACES :

- 1st Coat : One coat of suitable anticorrosion primer (i.e. Zinc Phosphate Primer White) .
2nd & 3rd Coat : Two coats of DL STARS finish coat by using brush 35% thinning by volume with water .

3. APPLICATION OF WOOD SURFACES :

- 1st Coat : One coat of GTC Wood Primer White.
2nd & 3rd Coat : Two coats of DL Cristal finish coat by using brush 35% thinning by volume with water ..

APPLICATION CONDITIONS :-

At a temperature ranging 5°C (41°F) to 40°C (104 °F) . Relative humidity is below 75%.

STORAGE & HANDLING :-

Product must be stored as per local regulations and should be kept in dry well ventilated location far from heat and direct sunlight. Can should be tightly closed after use. Mix well before use. Storage temperature range between 5°C (41°F) to 40°C (104 °F).

STANDARDS & APPROVALS:

Supportive information is available upon request to establish product compliance with a particular specification. **Please consult with GTC Technical Service Dept.**

SAFETY PRECAUTIONS:

The following notes should be considered when using/applying painting material:-

- Take precautions to prevent material entering the eyes (goggles should be worn, irrigate the eyes with water when become contaminated and obtain medical care at once).
- Take precautions to avoid skin contact (gloves should be worn, barrier cream should be used).
- Ensure that repeated contact of paint with skin is avoided.
- Provide adequate ventilation. (Face masks must be worn).
- Keep away from sparks and open flames (for solvent-based materials).

DISCLAIMER:

- The information given in this data sheet is for guidance only and is done to the best of our knowledge at the date of printing/issuing.
- GTC reserves the right to change the content of this data without any prior notice.
- Since we have no control over either the nature or condition of the substrate or different factors which effect the use and application of our products; therefore, no liability can be accepted on basis of this data sheet, unless we specifically agree in writing as to the suitability of the recommended product for the intended purpose; and furthermore, application of this product should be carried out under our control and direct supervision.
- Product data are subject to change without notice and become void five years from the date of issue.

PACKING : ♦ 2.5 ltr. Plastic Can.
ISSUANCE DATE : August 2017
ORIGIN : Manufacture in Kuwait by GTC Paints Company Ltd.
ADDRESS : **GTC PAINTS COMPANY LTD.**
P.O.Box 24445 Safat, 13105 Safat, Kuwait
Tel : 24710120/24710170 - Fax : 24761261 .
Email : sales @ gtcpaints.com