

# GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait  
Sabhan Tel.: 24710120 - Fax : 24761261  
Shuwaikh Tel.: 24848285 - Fax : 24837138  
Capital : K.D. 1,000,000 - C.R.: 20117



# شركة أصباغ جى تى سى المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت  
صباحان - تلفون : 24710120 - فاكس : 24761261  
الشويخ - تلفون : 24848285 - فاكس : 24837138  
رأس المال : 1,000,000 د.ك - س.ت : 20117

## GETASHINE

### PRODUCT DESCRIPTION:

A superior quality water-borne **High Lustre Emulsion Paint** based on a **Special Acrylic Copolymer** particularly formulated to offer a highly flexible, waterproof decorative and protective finish.

### SPECIAL FEATURES:

- ♦ A very pleasant lustre finish incorporated with a very good hiding power.
- ♦ Excellent flexibility.
- ♦ Waterproof Finish.
- ♦ Excellent decorative effects and application versatility.
- ♦ Unlike oil or alkyd based gloss paints, this product has minimum yellowing when used internally.
- ♦ Superior resistance to weathering conditions.
- ♦ Resistant to wet scrubbing and suitable for painting alkaline surfaces.
- ♦ Easy to apply.
- ♦ Due to its high build textured finish, this product tends to hide minor surface imperfections
- ♦ Thixotropic providing a high build finish.

### AREA OF USE:

- As an Exterior/Interior decorative and protective lustre emulsion finish coat suitable for application over concrete, walls, masonry, gypsum boards, bricks ... etc. i.e.,
- ♦ Interior walls and ceilings.
  - ♦ External concrete structure.
  - ♦ Areas subjected to wet conditions and high humidity (**bathrooms & kitchens**).
  - ♦ Perfectly suited as a protective coat over **GTC Textured System** where minimum dirt retention and dust is provided.
  - ♦ As a pleasant and shiny coat over Mosque Domes & significant architectural monuments.

### PRODUCT DATA:

FINISH	:	<b>GLOSSY</b> (Textured & Smooth)
COLOUR	:	According to <b>GTC COLOUR CARD RANGE</b> , (Special colours are available upon request).
VOLUME SOLIDS	:	45%
PRODUCT WEIGHT	:	1.20 Kg/ltr. Wet : 85-320 microns per coat depending upon required finish (approx. 3.3 - 12.6 mils)
REC. FILM THICKNESS	:	Dry : 40-150 microns per coat depending upon required finish (approx. 1.57 - 5.9 mils)
THEO. COVERAGE	:	11-3 m <sup>2</sup> /ltr. Practical coverage primarily depends upon nature/degree of surface porosity, method of application and site conditions.
FLASH POINT	:	Non-flammable (water-borne product)

# GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait  
Sabhan Tel.: 24710120 - Fax : 24761261  
Shuwaikh Tel.: 24848285 - Fax : 24837138  
Capital : K.D. 1,000,000 - C.R.: 20117



## شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت  
صباحان - تلفون: 24710120 - فاكس: 24761261  
الشويخ - تلفون: 24848285 - فاكس: 24837138  
رأس المال: 1,000,000 د.ك - س.ت: 20117

### DRYING TIME:

SUBSTRATE TEMPERATURE	TOUCH DRY	HARD DRY	OVERCOATING INTERVALS	
			MINIMUM	MAXIMUM
10 °C (50 °F)	4 hrs.	16 hrs.	8 hrs.	IND.
25 °C (77 °F)	2 hrs.	12 hrs.	4 hrs.	IND.
40 °C (104 °F)	1 hour	10 hrs.	3 hrs.	IND.

### SURFACE PREPARATION:

#### NEW SURFACES :

1. Degrease areas where grease, oil, soil and other surface contamination exist in accordance with **SSPC-SP1 Solvent Cleaning** . (Use **GTC002 Thinner**).
2. Wire brush/Mechanical Power Tool Clean areas where laitance, surface porosity and loosely adhering foreign material exist in accordance with **SSPC-SP2** and/or **SSPC-SP3 Standards**
3. Surfaces to be coated must be dry, clean and contamination free prior to paint application process.

#### OLD/PREVIOUSLY PAINTED SURFACES :

1. Degrease areas where grease, oil and other surface contamination exist in accordance with **SSPC-SP1 Solvent Cleaning**. (Use **GTC002 Thinner**).
2. Remove all blistered, cracked and brittle paint coats off the surface.
3. Detached coats with inadequate adhesion must be properly scraped-off to a firm edge.
4. Glossy paint coatings must be sanded/roughened to ensure proper intercoat adhesion characteristics with successive paint coatings.
5. Surfaces to be coated must be dry, clean and contamination free prior to paint application process.

### APPLICATION DETAILS:

REQUIRED FINISH	No. of Coats Recommended	Thinning %	Method of Application
SMOOTH	2-3 Coats *	30%	Brush, Roller, Spray, Airless Spray
TEXTURED	1 Coat Only*	N/A	Perforated Roller/ Hopper Gun
AS A PROTECTIVE COAT OVER ROLLTEX & TROWTEX AND SPATTER FINISHES	2 Coats	20-25%	Brush, Spray, Airless Spray

**Priming :** GTC Texture primer or with Acrylic Sealer.

\* It is recommended to apply GTC Base Coat White to promote adhesion.

**NOTE:** Excessive thinning will cause *Getashine* to loose its **thixotropic nature**.

### APPLICATION CONDITIONS :-

At a temperature ranging 5°C (41°F) to 40°C (104 °F) . Relative humidity is below 75%.

### STORAGE & HANDLING :-

Product must be stored as per local regulations and should be kept in dry well ventilated location far from heat and direct sunlight. Can should be tightly closed after use. Mix well before use. Storage temperature range between **5°C (41°F) to 40°C (104 °F)**.



## GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait  
Sabhan Tel.: 24710120 - Fax : 24761261  
Shuwaikh Tel.: 24848285 - Fax : 24837138  
Capital : K.D. 1,000,000 - C.R.: 20117



## شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت  
صباحان - تلفون: 24710120 - فاكس: 24761261  
الشويخ - تلفون: 24848285 - فاكس: 24837138  
رأس المال: 1,000,000 د.ك - س.ت: 20117

### **STANDARDS & APPROVALS:**

Supportive information is available upon request to establish an assessment to be acquired as with regards to product's compliance with/to a particular authority's queries / specifications. **Please consult with GTC Technical Service Dept.**

### **SAFETY PRECAUTIONS:**

The following notes should be considered when using/applying painting material:-

- Take precautions to prevent material entering the eyes (goggles should be worn, irrigate the eyes with water when become contaminated and obtain medical care at once).
- Take precautions to avoid skin contact (gloves should be worn, barrier cream should be used).
- Ensure that repeated contact of paint with skin is avoided.
- Provide adequate ventilation. (Face masks must be worn).
- Keep away from sparks and open flames (for solvent-based materials).

### **DISCLAIMER:**

- ◆ The information given in this data sheet is for guidance only and is done to the best of our knowledge at the date of printing/issuing.
- ◆ GTC reserves the right to change the content of this data without any prior notice.
- ◆ Since we have no control over either the nature or condition of the substrate or different factors which effect the use and application of our products; therefore, no liability can be accepted on basis of this data sheet, unless we specifically agree in writing as to the suitability of the recommended product for the intended purpose; and furthermore, application of this product should be carried out under our control and direct supervision.
- ◆ Product data are subject to change without notice and become void five years from the date of issue.

**PACKING** : ◆ Gallon  
◆ 18 Ltr. Drum  
◆ The final volume of colours produced will depend upon the content of each color.

**ISSUANCE DATE** : August 2017

**ORIGIN** : Manufacture in Kuwait by GTC Paints Company Ltd.

**ADDRESS** : **GTC PAINTS COMPANY LTD.**  
P.O.Box 24445 Safat, 13105 Safat, Kuwait  
Tel : 24710120/24710170 - Fax : 24761261 .  
Email : sales @ gtcpaints.com