

# GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait  
Sabhan Tel.: 24710120 - Fax : 24761261  
Shuwaikh Tel.: 24848285 - Fax : 24837138  
Capital : K.D. 1,000,000 - C.R.: 20117



# شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت  
صباحان - تلفون : 24710120 - فاكس : 24761261  
الشويخ - تلفون : 24848285 - فاكس : 24837138  
رأس المال : 1,000,000 د.ك - س.ت : 20117

## \* \* DL REFLECTO \* \*

### PRODUCT DESCRIPTION:

A water-borne decorative finish based on Acrylic copolymer, mixed with metallic pigments to gives surfaces an antiqued look. That produce highly original light mutations and stunning reflections.

### SPECIAL FEATURES:

- ☐ Excellent washability.
- ☐ Fully washable and water proof.
- ☐ Neither flammable nor hazards, being as mindful of environment as of personal health.
- ☐ Has luminous sheen, marked by bright metallic reflections.
- ☐ Easy to apply provide smooth, rich and water permeable film .

### AREA OF USE:

As a decorative finish for Interior/exterior new as well as old surfaces i.e.

- ☐ All kind of plasters, plaster boarded, gypsum boards.
- ☐ Iron surfaces primed using. White anticorrosion primer such as stairways, gates, and exposed iron ware parts.
- ☐ Wood surfaces primed using wood primer.

### PRODUCT DATA:

FINISH	:	<b><i>Smooth Metallic Reflection.</i></b>
COLOUR	:	According to <b>GTC COLOUR CARD</b> , Special colours are available upon request .
PRODUCT WEIGHT	:	1.12 Kg/Ltr.
THEO. COVERAGE	:	10 m <sup>2</sup> / ltr. per coat Practical coverage primarily depends upon nature/degree of surface porosity, method of application and site conditions.
FLASH POINT	:	Non-flammable (water-borne product)

### DRYING TIME:

SUBSTRATE TEMPERATURE	TOUCH DRY	HARD DRY	OVERCOATING INTERVALS	
			MINIMUM	MAXIMUM
10 °C (50 °F)	3 hrs.	5 hrs.	5 hrs.	IND.
25 °C (77 °F)	2 hrs.	4 hrs.	4 hrs.	IND.
40 °C (104 °F)	1 hour	3 hrs.	3 hrs.	IND.

### SURFACE PREPARATION:

Remove all dust, dirt, oil and grease contamination, loose particles, laitance and old paint...etc, the surface must be smooth and dry.

# GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait  
Sabhan Tel.: 24710120 - Fax : 24761261  
Shuwaikh Tel.: 24848285 - Fax : 24837138  
Capital : K.D. 1,000,000 - C.R.: 20117



# شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت  
صباحان - تلفون: 24710120 - فاكس: 24761261  
الشويخ - تلفون: 24848285 - فاكس: 24837138  
رأس المال: 1,000,000 د.ك - س.ت: 20117

## APPLICATION DETAILS:

### 1. APPLICATION OF CONCRETE/PLASTER WALLS :

- 1<sup>st</sup> Coat : One coat Acrylic Sealer 100% thinning by volume with water. **OR**  
Penetrol Sealer 25% thinning by volume with water.  
2<sup>nd</sup> Coat : One coat DL ART Primer matching the color of DL Reflecto finish coat or  
3<sup>rd</sup> & 4<sup>th</sup> Coat : White coats of DL Reflecto finish colour, by using brush no need of thinning, by  
spray thinning of 15-20% by volume 2 coats of DL Reflecto finish coat with  
water.

### 2. APPLICATION OF METALIC SURFACES :

- 1<sup>st</sup> Coat : One coat of suitable anticorrosion primer (i.e. Zinc Phosphate Primer White).  
2<sup>nd</sup> & 3<sup>rd</sup> Coat : Two coats of DL Reflecto finish coat.

### 3. APPLICATION OF WOOD SURFACES :

- 1<sup>st</sup> Coat : One coat of GTC Wood Primer White.  
2<sup>nd</sup> & 3<sup>rd</sup> Coat : Two coats of DL Reflecto finish coat.

## CLEANING:

For cleaning tools and equipment use fresh water only.

## APPLICATION CONDITIONS :-

At a temperature ranging 5°C (41°F) to 40°C (104 °F) . Relative humidity is below 75%.

## STORAGE & HANDLING :-

Product must be stored as per local regulations and should be kept in dry well ventilated location far from heat and direct sunlight. Can should be tightly closed after use. Mix well before use. Storage temperature range between 5°C (41°F) to 40°C (104 °F).

## STANDARDS & APPROVALS:

Supportive information is available upon request to establish product compliance with a particular specification. **Please consult with GTC Technical Service Dept.**

## SAFETY PRECAUTIONS:

The following notes should be considered when using/applying painting material:-

- Take precautions to prevent material entering the eyes (goggles should be worn, irrigate the eyes with water when become contaminated and obtain medical care at once).
- Take precautions to avoid skin contact (gloves should be worn, barrier cream should be used).
- Ensure that repeated contact of paint with skin is avoided.
- Provide adequate ventilation. (Face masks must be worn).
- Keep away from sparks and open flames (for solvent-based materials).

## DISCLAIMER:

- The information given in this data sheet is for guidance only and is done to the best of our knowledge at the date of printing/issuing.
- GTC reserves the right to change the content of this data without any prior notice.
- Since we have no control over either the nature or condition of the substrate or different factors which effect the use and application of our products; therefore, no liability can be accepted on basis of this data sheet, unless we specifically agree in writing as to the suitability of the recommended product for the intended purpose; and furthermore, application of this product should be carried out under our control and direct supervision.
- Product data are subject to change without notice and become void five years from the date of issue.

PACKING : ♦ 2.5 ltr. Plastic Can.  
ISSUANCE DATE : August 2017  
ORIGIN : Manufacture in Kuwait by GTC Paints Company Ltd.  
ADDRESS : **GTC PAINTS COMPANY LTD.**  
P.O.Box 24445 Safat, 13105 Safat, Kuwait  
Tel : 24710120/24710170 - Fax : 24761261 .  
Email : sales @ gtcpaints.com