

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون: 24710120 - فاكس: 24761261
الشويخ - تلفون: 24848285 - فاكس: 24837138
رأس المال: 1,000,000 د.ك - س.ت: 20117

* * DL ANTIGRAFFITI COATING * *

PRODUCT DESCRIPTION:

A water-borne coating based on modified Acrylic Resin. It is a perfect solution to protect the wall, painted or new, against disfigurement or graffiti with our ruin the wall.

SPECIAL FEATURES:

- ☐ Offering a total protection against spray paints, felt-tip pens or similar.
- ☐ Can be easily reapplied on the same surface.
- ☐ It is biodegradable, has a good resistance against atmospheric and chemical agents.
- ☐ Shows an excellent adhesion on different kind of materials.
- ☐ Neither harmful nor toxic for men and environment.

AREA OF USE:

As an protective coating for interior/exterior new as well as old surfaces i.e.

- ☐ All kind of concrete, plaster, terracotta, stones, marble and granite.

PRODUCT DATA:

FINISH : **MATT.**

COLOUR : **CLEAR**

PRODUCT WEIGHT : 1.1 Kg/Ltr.

THEO. COVERAGE : 8 m²/ ltr.for 3 coats

Practical coverage primarily depends upon nature/degree of surface porosity, method of application and site conditions.

FLASH POINT : Non-flammable (water-borne product)

DRYING TIME:

SUBSTRATE TEMPERATURE	TOUCH DRY	HARD DRY	OVERCOATING INTERVALS	
			MINIMUM	MAXIMUM
10 °C (50 °F)	3 hrs.	7 hrs.	7 hrs.	IND.
25 °C (77 °F)	2 hrs.	5 hrs.	5 hrs.	IND.
40 °C (104 °F)	1 hour	4 hrs.	4 hrs.	IND.

SURFACE PREPARATION:

Remove all dust, dirt, oil and grease contamination, loose particles, laitance and old paint...etc, the surface must be smooth and dry.

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون : 24710120 - فاكس : 24761261
الشويخ - تلفون : 24848285 - فاكس : 24837138
رأس المال : 1,000,000 د.ك - س.ت : 20117

APPLICATION DETAILS:

☐ USAGE:

Intended for a **2-3 coats over well prepared surfaces.** with . crossed layers and with at least 5-6 hours between 2 consecutive coats.

☐ METHOD OF APPLICATION :

DL Antigrffiti coating can be applied by Brush , Roller or conventional a spray .

CLEANING:

For cleaning tools and equipment use fresh water only.

APPLICATION CONDITIONS :-

At a temperature ranging 5°C (41°F) to 40°C (104 °F) . Relative humidity is below 75%.

STORAGE & HANDLING :-

Product must be stored as per local regulations and should be kept in dry well ventilated location far from heat and direct sunlight. Can should be tightly closed after use. Mix well before use. Storage temperature range between 5°C (41°F) to 40°C (104 °F).

STANDARDS & APPROVALS:

Supportive information is available upon request to establish product compliance with a particular specification. **Please consult with GTC Technical Service Dept.**

SAFETY PRECAUTIONS:

The following notes should be considered when using/applying painting material:-

- Take precautions to prevent material entering the eyes (goggles should be worn, irrigate the eyes with water when become contaminated and obtain medical care at once).
- Take precautions to avoid skin contact (gloves should be worn, barrier cream should be used).
- Ensure that repeated contact of paint with skin is avoided.
- Provide adequate ventilation. (Face masks must be worn).
- Keep away from sparks and open flames (for solvent-based materials).

DISCLAIMER:

- The information given in this data sheet is for guidance only and is done to the best of our knowledge at the date of printing/issuing.
- GTC reserves the right to change the content of this data without any prior notice.
- Since we have no control over either the nature or condition of the substrate or different factors which effect the use and application of our products; therefore, no liability can be accepted on basis of this data sheet, unless we specifically agree in writing as to the suitability of the recommended product for the intended purpose; and furthermore, application of this product should be carried out under our control and direct supervision.
- Product data are subject to change without notice and become void five years from the date of issue.

PACKING

- : ♦ 2.5 ltr. Can
- : ♦ 1 ltr. Plastic Can.

ISSUANCE DATE

: August 2017 .

ORIGIN

: Manufacture in Kuwait By GTC Paints Company Ltd.

ADDRESS

: **GTC PAINTS COMPANY LTD.**

P.O.Box 24445 Safat, 13105 Safat, Kuwait

Tel : 24710120/24710170 - Fax : 24761261 .

Email : sales @ gtepaints. com.