

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباح - تلفون : 24710120 - فاكس : 24761261
الشويخ - تلفون : 24848285 - فاكس : 24837138
رأس المال : 1,000,000 د.ك - س.ت : 20117

* * DL TRAVERTINE * *

PRODUCT DESCRIPTION:

DL Travertine is a decorative finish for indoor and outdoor use, based on seasoned slaked lime and natural fillers. Its all-natural makeup and its versatility, and depending on the application technique used, DL Travertine produces fascinating classical embellishments with travertine effect, or innovative embellishments with natural slate effect, applied as per suggested cycle.

SPECIAL FEATURES:

- ☐ It is thoroughly washable.
- ☐ Neither flammable nor hazardous, being as mindful of the environment as of personal health.
- ☐ Characterized by elegant patterns and shades that depending on the application technique.
- ☐ Stand out in a more or less uniform fashion, producing decorations that very closely resemble famed stones such as slate and travertine.

AREA OF USE:

As a decorative finish for interior and exterior new as well as old surfaces i.e. :-

<input type="checkbox"/>	All kinds of plaster, plasterboards, gypsum boards.
<input type="checkbox"/>	Ideal for creating beautiful "exposed stone" decorations, whether on indoor surfaces, facades, wainscoting, pillars or other outdoor surfaces.

PRODUCT DATA:

FINISH	:	Matt.
PRODUCT WEIGHT	:	1 Kg/Ltr.
THEO. COVERAGE	:	2.5-3.5 kg/ m ² Depending on substrate and desired effect .
FLASH POINT	:	Non-flammable (water-borne product)

DRYING TIME:

SUBSTRATE TEMPERATURE	TOUCH DRY	HARD DRY	OVERCOATING INTERVALS	
			MINIMUM	MAXIMUM
10 °C (50 °F)	3 hrs.	5 hrs.	5 hrs.	IND.
25 °C (77 °F)	2 hrs.	4 hrs.	4 hrs.	IND.
40 °C (104 °F)	1 hour	3 hrs.	3 hrs.	IND.

SURFACE PREPARATION:

Remove all dust, dirt, oil and grease contamination, loose particles, laitance and old paint...etc, the surface must be smooth and dry.

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون: 24710120 - فاكس: 24761261
الشويخ - تلفون: 24848285 - فاكس: 24837138
رأس المال: 1,000,000 د.ك - س.ت: 20117

APPLICATION DETAILS:

APPLICATION OF CONCRETE/PLASTER WALLS (Intend for two finish coats) :

- 1st Coat : One coat Acrylic Sealer 100% thinning by volume with water. **OR**
Penetrol Sealer 25% thinning by volume with water.
- 2nd Coat : One coat DL ART Primer 10% thinning by volume with water.
- 3rd Coat : There are two types of effect could be obtained :

a) Travertine effect :

Apply a first coat of Travertine using a stainless steel float, and spread the product evenly onto the surface. Once dried, use special adhesive tape to square up as desired, and then apply a second coat of KOLOSSOS in the same manner. Before it dries, proceed to "work the surface" (using a specific brush) based on the desired end result, and to flatten the coating with a stainless steel float. The product requires no thinning (no more than 5% water thinning is allowed) and must be blended mechanically before use.

b) Ardesia effect :

Apply a first coat of Travertine using a stainless steel float, and spread the product evenly onto the surface. Once dried, apply a second coat of KOLOSSOS in the same manner. Before it dries completely, proceed to "work the surface" with a special rubber roller. Then lightly flatten the surface with a stainless steel float.

NOTE :-

To obtain the desired effect and colour apply DL SYLOX OR DL OSSADINI decorative Finish in the colour of choice.

CLEANING:

For cleaning tools and equipment use fresh water only.

MIXING AND THINNING :-

- ☐ The product is ready to use and therefore requires no thinning.
- ☐ Mixing, stir thoroughly with a mechanical device before use.

APPLICATION CONDITIONS :-

At a temperature ranging 5°C (41°F) to 40°C (104 °F) . Relative humidity is below 75%.

STORAGE & HANDLING :-

Product must be stored as per local regulations and should be kept in dry well ventilated location far from heat and direct sunlight. Can should be tightly closed after use. Mix well before use. Storage temperature range between 5°C (41°F) to 40°C (104 °F).

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون : 24710120 - فاكس : 24761261
الشويخ - تلفون : 24848285 - فاكس : 24837138
رأس المال : 1,000,000 د.ك - س.ت : 20117

STANDARDS & APPROVALS:

Supportive information is available upon request to establish product compliance with a particular specification. **Please consult with GTC Technical Service Dept.**

SAFETY PRECAUTIONS:

The following notes should be considered when using/applying painting material:-

- (a) Take precautions to prevent material entering the eyes (goggles should be worn, irrigate the eyes with water when become contaminated and obtain medical care at once).
- (b) Take precautions to avoid skin contact (gloves should be worn, barrier cream should be used).
- (c) Ensure that repeated contact of paint with skin is avoided.
- (d) Provide adequate ventilation. (Face masks must be worn).
- (e) Keep away from sparks and open flames (for solvent-based materials).

DISCLAIMER:

- ♦ The information given in this data sheet is for guidance only and is done to the best of our knowledge at the date of printing/issuing.
- ♦ GTC reserves the right to change the content of this data without any prior notice.
- ♦ Since we have no control over either the nature or condition of the substrate or different factors which effect the use and application of our products; therefore, no liability can be accepted on basis of this data sheet, unless we specifically agree in writing as to the suitability of the recommended product for the intended purpose; and furthermore, application of this product should be carried out under our control and direct supervision.
- ♦ Product data are subject to change without notice and become void five years from the date of issue.

PACKING

- : ♦ 2.5 ltr. Can
- : ♦ 15 ltr. Drum

ISSUANCE DATE

: August 2017 .

ORIGIN

: Manufacture in Kuwait By GTC Paints Company Ltd.

ADDRESS

: **GTC PAINTS COMPANY LTD.**

P.O.Box 24445 Safat, 13105 Safat, Kuwait
Tel : 24710120/24710170 - Fax : 24761261 .
Email : sales @ gtcpaints. com.