

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جى تى سى المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون : 24710120 - فاكس : 24761261
الشويخ - تلفون : 24848285 - فاكس : 24837138
رأس المال : 1,000,000 د.ك - س.ت : 20117

DL WAX

PRODUCT DESCRIPTION:

DL WAX is a special protective water-borne finish with special waxes and water borne additives. It comes in classic version (transparent), one with Golden reflections, and one with Silver reflection.

SPECIAL FEATURES:

- ◆ Protect decoration finish specially stucco from dust and water.
- ◆ Neither flammable nor hazards, being as mindful of environment as of personal health.
- ◆ It has glossy finish and smooth.
- ◆ DL WAX Gold and Silver differ from the classic version for their golden and silver hues that stand out depending on the angle of view.
- ◆ Highly washable.

AREA OF USE:

As decorative finish for interior stucco application for lending surfaces bright and shiny look.

PRODUCT DATA:

FINISH	:	GLOSSY.
COLOUR	:	Classic - Clear Gold - reflection Silver - reflection Natural - Clear
PRODUCT WEIGHT	:	1 Kg/Ltr.
THEO. COVERAGE	:	15 m ² / ltr. per coat Depending on substrate and desired effect.
FLASH POINT	:	Non-flammable (water-borne product)

DRYING TIME:

SUBSTRATE TEMPERATURE	TOUCH DRY	HARD DRY	OVERCOATING INTERVALS	
			MINIMUM	MAXIMUM
10 °C (50 °F)	8 hrs.	10 hrs.	24 hrs.	IND.
25 °C (77 °F)	6 hrs.	8 hrs.	24 hrs.	IND.
40°C (104 °F)	5 hour	7 hrs.	24 hrs.	IND.

SURFACE PREPARATION:

The surface previously treated with stucco must be completely smooth, clean and dry.

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون: 24710120 - فاكس: 24761261
الشويخ - تلفون: 24848285 - فاكس: 24837138
رأس المال: 1,000,000 د.ك - س.ت: 20117

APPLICATION DETAILS:

Apply a coat of DL WAX with a dry cloth or swab; spread the product onto the surface, taking care to level the amount evenly. After about 30 minutes proceed to polish the surface manually with a special mechanical device and buffer.

After the second coat of stucco, when applying DL WAX Gold and Silver versions, we do not recommended full polishing with the stainless steel float. Rather It is best to leave slight, unpolished nuances that facilitate the absorption of the WAX.

CLEANING:

For cleaning tools and equipment use fresh water only.

APPLICATION CONDITIONS :-

At a temperature ranging 5°C (41°F) to 40°C (104 °F) . Relative humidity is below 75%.

STORAGE & HANDLING :-

Product must be stored as per local regulations and should be kept in dry well ventilated location far from heat and direct sunlight. Can should be tightly closed after use. Mix well before use. Storage temperature range between 5°C (41°F) to 40°C (104 °F).

STANDARDS & APPROVALS:

Supportive information is available upon request to establish product compliance with a particular specification. **Please consult with GTC Technical Service Dept.**

SAFETY PRECAUTIONS:

The following notes should be considered when using/applying painting material:-

- Take precautions to prevent material entering the eyes (goggles should be worn, irrigate the eyes with water when become contaminated and obtain medical care at once).
- Take precautions to avoid skin contact (gloves should be worn, barrier cream should be used).
- Ensure that repeated contact of paint with skin is avoided.
- Provide adequate ventilation. (Face masks must be worn).
- Keep away from sparks and open flames (for solvent-based materials).

DISCLAIMER:

- The information given in this data sheet is for guidance only and is done to the best of our knowledge at the date of printing/issuing.
- GTC reserves the right to change the content of this data without any prior notice.
- Since we have no control over either the nature or condition of the substrate or different factors which effect the use and application of our products; therefore, no liability can be accepted on basis of this data sheet, unless we specifically agree in writing as to the suitability of the recommended product for the intended purpose; and furthermore, application of this product should be carried out under our control and direct supervision.
- Product data are subject to change without notice and become void five years from the date of issue.

PACKING

- ♦ 2.5 ltr. Can
- ♦ 1 ltr. Plastic Can.

ISSUANCE DATE

: August 2017 .

ORIGIN

: Manufacture in Kuwait By GTC Paints Company Ltd.

ADDRESS

: **GTC PAINTS COMPANY LTD.**

P.O.Box 24445 Safat, 13105 Safat, Kuwait
Tel : 24710120/24710170 - Fax : 24761261 .
Email : sales @ gtcpaints. com.