

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون : 24710120 - فاكس : 24761261
الشويخ - تلفون : 24848285 - فاكس : 24837138
رأس المال : 1,000,000 د.ك - س.ت : 20117

* * DL GLAZE * *

PRODUCT DESCRIPTION:

Super Glaze is a transparent superior quality water based surface glazing compound designed to impart high sheen and protection to various surfaces.

SPECIAL FEATURES:

- ☐ Excellent exterior durability & hardness.
- ☐ Controllable gloss level.
- ☐ Water resistant.
- ☐ Can overcoat various finishes.
- ☐ Alkali resistant.

AREA OF USE:

As a Glaze over most substrates

- ☐ Most painted surfaces (Emulsion etc...)
- ☐ Concrete.
- ☐ Plaster.
- ☐ Texture finish.

PRODUCT DATA:

FINISH	: GLOSSY & SILK FINISH .
COLOUR	: CLEAR.
VOLUME SOLIDS	: 40% .
PRODUCT WEIGHT	: 1.1 Kg/Ltr.
THEO. COVERAGE	: Depends on surface & gloss level.
FLASH POINT	: Non-flammable (water-borne product)

DRYING TIME:

SUBSTRATE TEMPERATURE	TOUCH DRY	HARD DRY	OVERCOATING INTERVALS	
			MINIMUM	MAXIMUM
10 °C (50 °F)	2 hrs.	6 hrs.	6 hrs.	IND.
25 °C (77 °F)	30 min	4 hrs.	5 hrs.	IND.
40 °C (104 °F)	15 min.	2 hour	4 hrs.	IND.

SURFACE PREPARATION:

Surface to be coated must be dry, clean and contamination free prior to paint application process.

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون : 24710120 - فاكس : 24761261
الشويخ - تلفون : 24848285 - فاكس : 24837138
رأس المال : 1,000,000 د.ك - س.ت : 20117

APPLICATION DETAILS:

☐ USAGE:

Intend for a single or multicoat application to the desired gloss level.

☐ MIXING AND THINNING:

Material must be properly mixed with fresh water to the correct painting consistency.

☐ METHOD OF APPLICATION :

Super Glaze can be applied by Brush, Roller, conventional & Airless Spray.

☐ CLEANING :

For cleaning tools and equipment use fresh water only.

APPLICATION CONDITIONS :-

At a temperature ranging 5°C (41°F) to 40°C (104 °F) . Relative humidity is below 75%.

STORAGE & HANDLING :-

Product must be stored as per local regulations and should be kept in dry well ventilated location far from heat and direct sunlight. Can should be tightly closed after use. Mix well before use. Storage temperature range between 5°C (41°F) to 40°C (104 °F).

SAFETY PRECAUTIONS:

The following notes should be considered when using/applying painting material:-

- Take precautions to prevent material entering the eyes (goggles should be worn, irrigate the eyes with water when become contaminated and obtain medical care at once).
- Take precautions to avoid skin contact (gloves should be worn, barrier cream should be used).
- Ensure that repeated contact of paint with skin is avoided.
- Provide adequate ventilation. (Face masks must be worn).
- Keep away from sparks and open flames (for solvent-based materials).

DISCLAIMER:

- ♦ The information given in this data sheet is for guidance only and is done to the best of our knowledge at the date of printing/issuing.
- ♦ GTC reserves the right to change the content of this data without any prior notice.
- ♦ Since we have no control over either the nature or condition of the substrate or different factors which effect the use and application of our products; therefore, no liability can be accepted on basis of this data sheet, unless we specifically agree in writing as to the suitability of the recommended product for the intended purpose; and furthermore, application of this product should be carried out under our control and direct supervision.
- ♦ Product data are subject to change without notice and become void five years from the date of issue.

PACKING	:	<input type="checkbox"/> 1 LTR.
ISSUANCE DATE	:	<input type="checkbox"/> 2.5 Ltr. Gallon
ORIGIN	:	Manufacture in Kuwait By GTC Paints Company Ltd.
ADDRESS	:	GTC PAINTS COMPANY LTD. P.O.BOX 24445 Safat, 13105 Safat, Kuwait. Tel : 24710120/24710170 - Fax : 24761261. Email : sales @ gtcpaints.com .