

## GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait  
Sabhan Tel.: 24710120 - Fax : 24761261  
Shuwaikh Tel.: 24848285 - Fax : 24837138  
Capital : K.D. 1,000,000 - C.R.: 20117



## شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت  
صباحان - تلفون: 24710120 - فاكس: 24761261  
الشويخ - تلفون: 24848285 - فاكس: 24837138  
رأس المال: 1,000,000 د.ك - س.ت: 20117

# Wall Putty

### PRODUCT DESCRIPTION :-

A specially formulated water born interior wall putty based on Acrylic copolymer mixed with suitable pigment and extenders to match the speed of modern building construction to obtain good leveling and coating sub- straits.

### SPECIAL FEATURES :-

- Ready for use where no mixing is required in site.
- Can be applied over non-plastered concrete and masonry surfaces.
- Non toxic, non flammable and sound/absorbent coat.
- Easy to sand and provides a smooth finish.
- Very good hiding power and tends to hide minor surface imperfections.
- Dries to form a surface tolerant and compatible substrate with all types of paints.

### AREA OF USE :-

As an interior leveling and putty material over a variety of new and old substrates i.e.

- Concrete structure.
- Gypsum Boards/Plastered Boards.
- Fairface concrete.
- New Construction ceilings.

### PRODUCT DATA :-

Finish	: Matt.
Colour	: White.
Volume Solids	: 50 %.
Product Weight	: 1.55 KG/LTR.
Theoretical Coverage	: Approx. 2M2/KG depending upon applied thickness. Practical coverage primarily depends upon nature/degree of surface porosity, method of application and site conditions.
Flash Point	: Non-flammable (water-born product).
Rec.Film thickness	: Up to 400 microns per application.

## GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait  
Sabhan Tel.: 24710120 - Fax : 24761261  
Shuwaikh Tel.: 24848285 - Fax : 24837138  
Capital : K.D. 1,000,000 - C.R.: 20117



## شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت  
صباحان - تلفون: 24710120 - فاكس: 24761261  
الشويخ - تلفون: 24848285 - فاكس: 24837138  
رأس المال: 1,000,000 د.ك - س.ت: 20117

### SURFACE PREPARATION :-

- All surfaces must be clean, dry and free from contamination i.e. dust, oil, grease, mould, mildew or loosely adhering materials ...etc.
- For new concrete, substrate protrusions such as nibs, tins.. etc must be removed.

### APPLICATION DETAILS :-

- Purpose of usage :-**  
Intended for two or three coat applications over suitably sealed/primed surfaces.
- Mixing and thinning :-**  
Ready to be used, no thinning is required.
- Method of application :-**  
GTC Wall Putty can be applied by trowel, putty knife and steel scraper.

### **NOTES :-**

- Apply the putty material in successive thin layers, sanding is required between layers after a minimum of 5-6 hrs. to achieve perfect smoothness and adhesion.
- Don't exceed recommended film thickness as this will result in poor adhesion, cracking of the applied painting system.  
(Glossy surfaces should be roughened until gloss fades away).

### **CLEANING :-**

For cleaning tools and equipments use fresh water only.

### APPLICATION CONDITIONS :-

At a temperature ranging 5°C (41°F) to 40°C (104 °F) . Relative humidity is below 75%.

### STORAGE & HANDLING :-

Product must be stored as per local regulations and should be kept in dry well ventilated location far from heat and direct sunlight. Can should be tightly closed after use. Mix well before use. Storage temperature range between 5°C (41°F) to 40°C (104 °F).

## GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait  
Sabhan Tel.: 24710120 - Fax : 24761261  
Shuwaikh Tel.: 24848285 - Fax : 24837138  
Capital : K.D. 1,000,000 - C.R.: 20117



## شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت  
صباحان - تلفون: 24710120 - فاكس: 24761261  
الشويخ - تلفون: 24848285 - فاكس: 24837138  
رأس المال: 1,000,000 د.ك - س.ت: 20117

### SAFETY PRECAUTIONS:

The following notes should be considered when using/applying material;-

- Take precautions to prevent material entering the eyes (goggles should be worn, irrigate the eyes with water when become contaminated and obtain medical care at once).
- Take precautions to avoid skin contact (gloves should be worn, barrier cream should be used).
- Ensure that repeated contact of paint with skin is avoided.
- Provide adequate ventilation. (Face masks must be worn).
- Keep away from sparks and open flame (for Solvent-based materials).

### DISCLAIMER:

- The information given in this data sheet is for guidance only and is done to the best of our knowledge at the date of printing/issuing.
- GTC reserves the right to change the content of this data without any prior notice.
- Since we have no control over either the nature or condition of the substrate or different factors which affect the use and application of our products; therefore, no liability can be accepted on basis of this data sheet, unless we specifically agree in writing from us as to the suitability of the recommended product for the intended purpose; and furthermore, application of this product should be carried out under our control and direct supervision.
- Product data are subject to change without notice and become void five years from the date of issue.

**PACKING** : ♦ 25 kg Drums/Nylon Bags.  
**ISSUANCE DATE** : August 2017 .  
**ORIGIN** : Manufacture in Kuwait By GTC Paints Company Ltd.  
**ADDRESS** : **GTC PAINTS COMPANY LTD.**

P. O. Box 24445 Safat, 13105 Safat, Kuwait

Tel : 24710120/24710170 - Fax : 24761261 .

Email : sales @ gtcpaints.com