

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون : 24710120 - فاكس : 24761261
الشويخ - تلفون : 24848285 - فاكس : 24837138
رأس المال : 1,000,000 د.ك - س.ت : 20117

** GETACRYL **

PRODUCT DESCRIPTION:

Getacryl is a one pack solvent-base coating based on an Acrylic Resin with excellent resistance to alkalies. It is formulated for application on concrete, masonry, mineral substrates, textured finishes etc....

SPECIAL FEATURES:

- ♦ Very good gloss and flow adhesion.
- ♦ Very good alkali resistance.
- ♦ Very good exterior durability
- ♦ Fast drying
 - ♦ Superior colour retention .
- ♦ Extremely tough flexible films.

AREA OF USE:

As an Exterior/Interior decorative and protective finish coat offering an extremely hard/flexible film over concrete, steel, textured paints .

PRODUCT DATA:

FINISH	:	GLOSSY .
COLOUR	:	White & GTC Colour Card Range. Special colours are available upon request .
VOLUME SOLIDS	:	45% .
PRODUCT WEIGHT	:	1.2 kg/ltr.
REC. FILM THICKNESS	:	Wet : 110 microns per coat (approx 4.37 mil) Dry : 50 microns per coat (approx 2 mil)
THEO. COVERAGE	:	9 m ² / ltr. Practical coverage primarily depends upon nature/degree of surface porosity, method of application and site conditions.
FLASH POINT	:	Greater than 23°C (73°F).

DRYING TIME:

SUBSTRATE TEMPERATURE	TOUCH DRY	HARD DRY	OVERCOATING INTERVALS	
			MINIMUM	MAXIMUM
10 °C (50 °F)	4 hrs	16 hrs.	14 hrs.	IND.
25 °C (77 °F)	3 hrs	12 hrs.	10 hrs.	IND.
40 °C (104 °F)	2 hrs	10 hrs	8 hrs.	IND.

SURFACE PREPARATION:

- DEGREE OILY/GREASY SURFACES IN ACCORDANCE WITH SSPC-SP1 CLEANING.
- CONCRETE/CEMENT SURFACES SHOULD BE SOUND CLEAN AND COMPLETELY CURED AND FREE FROM SALTS AND LAITANCE.
- TEXTURED SURFACES MUST BE CLEAN/DRY AND SOUND.

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون : 24710120 - فاكس : 24761261
الشويخ - تلفون : 24848285 - فاكس : 24837138
رأس المال : 1,000,000 د.ك - س.ت : 20117

APPLICATION DETAILS:

- ♦ **purpose of usage :**
Intended for a two or three finish coats application over suitably sealed/primed, puttied and undercoated surfaces.
- ♦ **mixing and thinning :**
Material must be properly mixed and is recommended for thinning with GTC005 Thinner as per below table:-

APPLICATION METHOD	BRUSH/ROLLER	CONV.SPRAY	AIRLESS SPRAY
Thinning by volume(% max.)	15 %	25 %	5 %

- ♦ **note :**
For external usage, it is not recommended to apply Interior Putty material.
- ♦ **cleaning :**
For cleaning tools and equipments use GTC005 Thinner.

APPLICATION CONDITIONS :-

At a temperature ranging 5°C (41°F) to 40°C (104 °F) . Relative humidity is below 75%.

STORAGE & HANDLING :-

Product must be stored as per local regulations and should be kept in dry well ventilated location far from heat and direct sunlight. Can should be tightly closed after use. Mix well before use. Storage temperature range between 5°C (41°F) to 40°C (104 °F).

STANDARDS & APPROVALS:

Supportive information is available upon request to establish product compliance with a particular specification. Please consult with GTC Technical Service Dept.

SAFETY PRECAUTIONS:

- The following notes should be considered when using/applying painting material:-
- (a) Take precautions to prevent material entering the eyes (goggles should be worn, irrigate the eyes with water when become contaminated and obtain medical care at once).
 - (b) Take precautions to avoid skin contact (gloves should be worn, barrier cream should be used).
 - (c) Ensure that repeated contact of paint with skin is avoided.
 - (d) Provide adequate ventilation. (Face masks must be worn).
 - (e) Keep away from sparks and open flames (for solvent-based materials).

DISCLAIMER:

- ♦ The information given in this data sheet is for guidance only and is done to the best of our knowledge at the date of printing/issuing.
- ♦ GTC reserves the right to change the content of this data without any prior notice.
- ♦ Since we have no control over either the nature or condition of the substrate or different factors which effect the use and application of our products; therefore, no liability can be accepted on basis of this data sheet, unless we specifically agree in writing as to the suitability of the recommended product for the intended purpose; and furthermore, application of this product should be carried out under our control and direct supervision.
- ♦ Product data are subject to change without notice and become void five years from the date of issue.

PACKING : ♦ Gallon
: ♦ 18 Ltr. Drum
ISSUANCE DATE : August 2017
ORIGIN : Manufacture in Kuwait by GTC Paints Company Ltd.
ADDRESS : GTC PAINTS COMPANY LTD.
P.O.Box 24445 Safat, 13105 Safat, Kuwait
Tel : 24710120/24710170 - Fax : 24761261 .
Email : sales @ gtcpaints.com