

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جى تى سى المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون: 24710120 - فاكس: 24761261
الشويخ - تلفون: 24848285 - فاكس: 24837138
رأس المال: 1,000,000 د.ك - س.ت: 20117

GET-A-SEAL CL-50 A/C Duct Canvas Coating & Adhesive

PRODUCT DESCRIPTION

Get-A-Seal CL-50 is an adhesive used for various insulation material such as woven glass fiber, fabric, canvas etc. It has coating properties allowing it to be used as such.

SPECIAL FEATURES

- ☐ Is a non flammable when wet.
- ☐ Is water based.
- ☐ Has both properties of coating and adhesive.
- ☐ Has a flexible film.

AREA OF USES

- ☐ Get-A-Seal CL-50 is used for bonding canvas and cloth to many insulated surfaces.
- ☐ For bonding laps of fibrous and woven glass cloths on pipe insulation.
- ☐ A coating over all the above fabrics and over plastic foam material such as polystyrene.

PRODUCT DATA

Colour	: White
Consistency	: Viscous Liquid.
Specific Gravity	: 1.25 + 0.05 KG/LTR.
Drying Time	: Touch dry 2 hours, drying time depends upon film thickness and temperature.
Coverage	: 2 M ² /kg Per One Coat
Bonding Canvas	: 4 M ² /kg
No of Coats	: Two coats are recommended.

APPLICATION DETAILS

- ☐ **Surface preparation**
The surface to be coated must be clean, dry, free of oil and grease.
- ☐ **Application of Adhesive**
CL-50 is easily applied by brush/roller or spray. Diluted CL-50 some time is used for dipping canvas for certain applications.

APPLICATION CONDITIONS :-

At a temperature ranging 5°C (41°F) to 40°C (104 °F) . Relative humidity is below 75%.

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون : 24710120 - فاكس : 24761261
الشويخ - تلفون : 24848285 - فاكس : 24837138
رأس المال : 1,000,000 د.ك - س.ت : 20117

STORAGE & HANDLING :-

Product must be stored as per local regulations and should be kept in dry well ventilated location far from heat and direct sunlight. Can should be tightly closed after use. Mix well before use. Storage temperature range between **5°C (41°F) to 40°C (104 °F)**.

STANDARDS & APPROVALS

Supportive information is available upon request.
Please consult with GTC Technical Service Dept.

SAFETY PRECAUTIONS:

The following notes should be considered when using/applying material:-

- Take precautions to prevent material entering the eyes (goggles should be worn, irrigate the eyes with water when become contaminated and obtain medical care at once).
- Take precautions to avoid skin contact (gloves should be worn, barrier cream should be used).
- Ensure that repeated contact of paint with skin is avoided.
- Provide adequate ventilation. (Face masks must be worn).
- Keep away from sparks and open flames (for solvent-based materials).

DISCLAIMER:

- The information given in this data sheet is for guidance only and is done to the best of our knowledge at the date of printing/issuing.
- GTC reserves the right to change the content of this data without any prior notice.
- Since we have no control over either the nature or condition of the substrate or different factors which affect the use and application of our products; therefore, no liability can be accepted on basis of this data sheet, unless we specifically agree in writing from us as to the suitability of the recommended product for the intended purpose; and furthermore, application of this product should be carried out under our control and direct supervision.
- Product data are subject to change without notice and become void five years from the date of issue.

PACKING

- : ☐ 4 KG Gallon.
- : ☐ 20 KG Drums.

ISSUANCE DATE

: August 2017 .

ORIGIN

: Manufacture in Kuwait By GTC Paints Company Ltd.

ADDRESS

: **GTC PAINTS COMPANY LTD.**

P. O. Box 24445 Safat, 13105 Safat, Kuwait

Tel : 24710120/24710170 - Fax : 24761261 .

Email : sales @ gtcpaints.com