

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جى تى سى المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون : 24710120 - فاكس : 24761261
الشويخ - تلفون : 24848285 - فاكس : 24837138
رأس المال : 1,000,000 د.ك - س.ت : 20117

GETEX N.F. Non-Flammable A/C Duct Adhesive

PRODUCT DESCRIPTION

Getex N.F. is a high quality chlorinated solvent based specialty adhesive designed to bond duct insulation material.

SPECIAL FEATURES

- ☐ Resistant to humidity.
- ☐ Withstands high wind speeds.
- ☐ Provides excellent bond strengths with insulation material.
- ☐ Non-Flammable when wet.

AREA OF USE

Due A/C Ducts to be insulated with e.g. Fiberglass, cork, polyurethane...etc.

PRODUCT DATA

Colour	: Amber.
Application	: Brush, trowel, roller.
Consistency	: Liquid.
Odour	: Organic solvent Odour .
Solvent type	: Non-flammable chlorinated solvent .
Coverage	: 4 M ² /kg Approx.

APPLICATION OF ADHESIVE/ASSEMBLY

- ☐ Apply a thin layer of adhesive by brush or trowel. When touch dry the coated surfaces can be positioned and pressed together.
- ☐ Use solvents for cleaning brushes and equipment.

APPLICATION CONDITIONS :-

At a temperature ranging 5°C (41°F) to 40°C (104 °F) . Relative humidity is below 75%.

STORAGE & HANDLING :-

Product must be stored as per local regulations and should be kept in dry well ventilated location far from heat and direct sunlight. Can should be tightly closed after use. Mix well before use. Storage temperature range between 5°C (41°F) to 40°C (104 °F).

GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait
Sabhan Tel.: 24710120 - Fax : 24761261
Shuwaikh Tel.: 24848285 - Fax : 24837138
Capital : K.D. 1,000,000 - C.R.: 20117



شركة أصباغ جى تى سى المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت
صباحان - تلفون : 24710120 - فاكس : 24761261
الشويخ - تلفون : 24848285 - فاكس : 24837138
رأس المال : 1,000,000 د.ك - س.ت : 20117

SAFETY AND ENVIRONMENT

- ☐ Ventilate working area well.
- ☐ Personal protective materials such as special solvents masks, gloves and goggles should be used.
- ☐ Materials leftovers should be discarded in the proper way as per prevailing environmental regulations.
- ☐ Keep container closed when not in use to prevent solvent evaporation.

STANDARDS & APPROVALS

Supportive information is available upon request.

Please consult with GTC Technical Service Dept.

SAFETY PRECAUTIONS:

The following notes should be considered when using/applying material:-

- (a) Take precautions to prevent material entering the eyes (goggles should be worn, irrigate the eyes with water when become contaminated and obtain medical care at once).
- (b) Take precautions to avoid skin contact (gloves should be worn, barrier cream should be used).
- (c) Ensure that repeated contact of paint with skin is avoided.
- (d) Provide adequate ventilation. (Face masks must be worn).
- (e) Keep away from sparks and open flames (for solvent-based materials).

DISCLAIMER:

- The information given in this data sheet is for guidance only and is done to the best of our knowledge at the date of printing/issuing.
- GTC reserves the right to change the content of this data without any prior notice.
- Since we have no control over either the nature or condition of the substrate or different factors which affect the use and application of our products; therefore, no liability can be accepted on basis of this data sheet, unless we specifically agree in writing from us as to the suitability of the recommended product for the intended purpose; and furthermore, application of this product should be carried out under our control and direct supervision.
- Product data are subject to change without notice and become void five years from the date of issue.

PACKING

: ☐ 4 kg Gallon

ISSUANCE DATE

: August 2017 .

ORIGIN

: Manufacture in Kuwait By GTC Paints Company Ltd.

ADDRESS

: **GTC PAINTS COMPANY LTD.**

P. O. Box 24445 Safat, 13105 Safat, Kuwait

Tel : 24710120/24710170 - Fax : 24761261 .

Email : sales @ gtcpaints.com