

# GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait  
Sabhan Tel.: 24710120 - Fax : 24761261  
Shuwaikh Tel.: 24848285 - Fax : 24837138  
Capital : K.D. 1,000,000 - C.R.: 20117



# شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت  
صباحان - تلفون : 24710120 - فاكس : 24761261  
الشويخ - تلفون : 24848285 - فاكس : 24837138  
رأس المال : 1,000,000 د.ك - س.ت : 20117

## \* \* DL DECORATIVE LINE PAINTS \* \*

### (Perl, Ridescenti, Style, Sence)

#### PRODUCT DESCRIPTION:

A water-borne decorative paint finishes paints based on modified Acrylic Copolymer, mixed with micaceous and metallic pigments to provide an innovative and extra ordinary beauty decorative finishes.

#### SPECIAL FEATURES:

- ☐ Easy and fast to apply .
- ☐ Excellent washability.
- ☐ Neither flammable nor hazards, being as mindful of the environment as of personal health.
- ☐ Has luminous sheen, marked by bright metallic reflections.

#### AREA OF USE:

As a decorative finish is ideal for interior new as well as old surfaces i.e.

- ☐ All kind of plasters, plaster boards, gypsum boards.
- ☐ Wood surfaces primed using wood primer.
- ☐ Old Paints.

#### PRODUCT DATA:

FINISH	:	Smooth Perlescent, and Metallic Reflection.
COLOUR	:	According to GTC COLOUR CARD, DL-DECORATIVE LINE CATALOGUE FOR EACH PRODUCT. Special colours are available upon request .
PRODUCT WEIGHT	:	1.03 – 1.1 Kg/Ltr.
THEO. COVERAGE	:	8 m <sup>2</sup> / ltr. per coat Practical coverage primarily depends upon nature/degree of surface porosity, method of application and site conditions.
FLASH POINT	:	Non-flammable (water-borne product)

#### DRYING TIME:

SUBSTRATE TEMPERATURE	TOUCH DRY	HARD DRY	OVERCOATING INTERVALS	
			MINIMUM	MAXIMUM
10 °C (50 °F)	3 hrs.	7 hrs.	5 hrs.	IND.
25 °C (77 °F)	2 hrs.	6 hrs.	4 hrs.	IND.
40 °C (104 °F)	1 hour	5 hrs.	3 hrs.	IND.

**Note : -** Complete Drying 2-3 days.

**Dilution :** Ready made, no need.

#### SURFACE PREPARATION:

Remove all dust, dirt, oil and grease contamination, loose particles, laitance and old paint...etc, the surface must be clean and dry.

# GTC Paints Company Ltd.

P.O. Box: 24445 Safat - 13105 - Kuwait  
Sabhan Tel.: 24710120 - Fax : 24761261  
Shuwaikh Tel.: 24848285 - Fax : 24837138  
Capital : K.D. 1,000,000 - C.R.: 20117



# شركة أصباغ جي تي سي المحدودة

ص.ب: 24445 الصفاة - 13105 - الكويت  
صباحان - تلفون : 24710120 - فاكس : 24761261  
الشويخ - تلفون : 24848285 - فاكس : 24837138  
رأس المال : 1,000,000 د.ك - س.ت : 20117

## APPLICATION DETAILS:

- 1<sup>st</sup> Application : Two coats DL ART Primer according to the colour required.  
2<sup>nd</sup> Application : One coat of finish product required.

## APPLICATION METHOD FOR FINISH COAT :

- 1) On the matching colour of DL-ART PRIMER apply with "GTC Decorative Line" brush using cross hatch strokes covering an area of approx 1-2 m<sup>2</sup> blend then the decoration with the dry brush.
- 2) After about 5-10 minutes create the décor by smoothing the surface with the special GTC DL Spatula.

## CLEANING:

For cleaning tools and equipment use fresh water only.

## APPLICATION CONDITIONS :-

At a temperature ranging 5°C (41°F) to 40°C (104 °F) . Relative humidity is below 75%.

## STORAGE & HANDLING :-

Product must be stored as per local regulations and should be kept in dry well ventilated location far from heat and direct sunlight. Can should be tightly closed after use. Mix well before use. Storage temperature range between 5°C (41°F) to 40°C (104 °F).

## STANDARDS & APPROVALS:

Supportive information is available upon request to establish product compliance with a particular specification. **Please consult with GTC Technical Service Dept.**

## SAFETY PRECAUTIONS:

The following notes should be considered when using/applying painting material:-

- (a) Take precautions to prevent material entering the eyes (goggles should be worn, irrigate the eyes with water when become contaminated and obtain medical care at once).
- (b) Take precautions to avoid skin contact (gloves should be worn, barrier cream should be used).
- (c) Ensure that repeated contact of paint with skin is avoided.
- (d) Provide adequate ventilation. (Face masks must be worn).
- (e) Keep away from sparks and open flames (for solvent-based materials).

## DISCLAIMER:

- ♦ The information given in this data sheet is for guidance only and is done to the best of our knowledge at the date of printing/issuing.
- ♦ GTC reserves the right to change the content of this data without any prior notice.
- ♦ Since we have no control over either the nature or condition of the substrate or different factors which effect the use and application of our products; therefore, no liability can be accepted on basis of this data sheet, unless we specifically agree in writing as to the suitability of the recommended product for the intended purpose; and furthermore, application of this product should be carried out under our control and direct supervision.
- ♦ Product data are subject to change without notice and become void five years from the date of issue.

## PACKING

- : ♦ 2.5 ltr. Can  
: ♦ 1 ltr. Plastic Can.

## ISSUANCE DATE

: August 2017 .

## ORIGIN

: Manufacture in Kuwait By GTC Paints Company Ltd.

## ADDRESS

: **GTC PAINTS COMPANY LTD.**

P.O.Box 24445 Safat, 13105 Safat, Kuwait

Tel : 24710120/24710170 - Fax : 24761261 .

Email : sales @ gtcpaints. com.